COMPACT GUMMY DEPOSITING SYSTEM



Portable Modular Frame with Integrated Kitchen & Conveyor

GT10.2



• FEATURES

- Portable Stainless Steel Frame on Casters with Integrated Kitchen, Conveyor & Depositor
- New Silicone Molds with Internal Stainless Steel
 Reinforcement (Robust 3 Pounds Each!)
- Precision Servo Pump Accuracy +/- 2% by Weight - Best in Class
- 20 Liter Jacketed Overhead Cooking & Mixing Vessel w/ Side & Bottom Teflon Scrapers
- Adjustable Tilt-Tank for Ease of Transferring Syrup to Depositor

- Servo-Cleated Conveyor for Auto Indexing of Tray / Molds through Depositor
- 20 item Batch Recipe Storage. HMI Control Interface on both Depositor & Kitchen
- 10 Pistons Depositor Rated at Max 25 Deposits / min or 10,000 gumies / hr (Dependent on Gummy Size)
- Easy Ejection Pneumatic De-molding Station with Optional Modular & Portable Drying Tray & Cart System
- Single Deposit Max Delivery of 4.5 ml Triple Deposit Capable
- All GMP, FDA Approved Stainless Steel Contact Parts

GT10.2 COMPACT GUMMY DEPOSITING SYSTEM









· DEPOSITOR ·

· DEMOLDER ·


20 L KETTLE ·







TECHNICAL **SPECIFICATIONS**

| MODEL: | GT10.2 |
|-------------------------------|---|
| Production Capacity: | 10,000 deposits / hr |
| Power Requirement: | 230V / 1ph / 60Hz |
| Power Consumption: | 20 Amps |
| Room Requirements for System: | |
| – Room Temperature: | 22~25°C |
| – Humidity: | ≤50% RH |
| Coating System Size: | W 38" x L 50" H 63" |
| Estimated Weight: | Approx. 500 lbs (all components included) |







1 YEAR WARRANTY

905 E. Salter Dr. Phoenix AZ 85024

info@capplustech.com

602-688-4044

gummytechnologies.com